

N800

SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.

- Standard N series has a narrow frame and compact mounting base.
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly
- Constant Tension is available – consult factory.



Optional TR roller position shown

For:

- Fuel Dispensing
(Consult Factory)

- Waste Oil Evacuation
- Air/Water

Parts Drawing – ISO 81

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Reel Dimensions***								
	feet			lb.	kg.		in.								
	m.						NET	SHIP	A	B	C	E	F	G	H
	I.D. (in)	3/4"	1"												
	I.D. (mm)	19	25												
	O.D. (in)	1-9/32"	1-9/16"												
	O.D. (mm)	33	40												
N816-19-20J		25	15	75	91*	N204	10	4	10.5	20.75	13	20	10.62	8	
		8	5	34	41		254	102	267	527	330	508	270	203	
N818-23-24J		50	25	87	100	N206	12	6	10.5	23.75	15	24	12.62	10	
		15	8	39	45		305	152	267	603	381	610	321	254	
N816-25-26B		60	35	96	131	N204	10	4	10.5	25.25	13	26	13.62	8	
		18	11	44	59		254	102	267	641	330	660	346	203	
N818-25-26B		70	50	102	137	N206	12	6	10.5	25.25	15	26	13.62	10	
		21	15	46	62		305	152	267	641	381	660	346	254	

Notes:

1. Specifications subject to change.
2. Reels models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. **Finish:** refer to Page 4.

5. Be sure to check dimensions and weights prior to ordering.

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

* When shipped as a parcel package (via Fed-Ex or UPS Ground).
 *** x,y indicate mounting holes. See page 2

