

IMPORTANT: OPW products should be used in compliance with applicable federal, state, provincial, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and materials to be handled. OPW MAKES NO WARRANTY OF FITNESS FOR A PARTICULAR USE. All illustrations and specifications in this literature are based on the latest product information available at the time of publication. OPW reserves the right to make changes at any time in prices, materials, specifications and models and to discontinue models without notice or obligation.



OPW 23 Series Open Atmospheric Vent (23-0044 23-0033 23-0055)



Open Atmospheric Vents are installed on the top of vent pipes from underground or aboveground fuel storage tanks. The vent cap and internal wire screen are designed to protect the tank vent lines against intrusion and blockage from water, debris or insects. These vents are always open to atmosphere and allow any pressure or vacuum in the tank to vent.

Features

- **Reliable Service** – Vent cap drain spouts extend outward to deter rainwater entry.
- **Corrosion-Resistant Construction** – Aluminum body and cap assure a long service life.
- **Easy Installation** – The 23 is available in 2" and 3" slip-on models that provide for attachment to the vent line with set screws.
- **Complies with NFPA 30 Requirements** – for venting gasoline vapors upward.
- **High Maximum Flow Rate** – 7000 SCFH at 2 psi pressure drop.
- **40-Mesh Brass Wire Screen** – Helps prevent debris and insects from entering the tank vent lines.

Materials

Body: aluminum

Screen: 40-mesh brass

Set Screws: brass

