

IMPORTANT: OPW products should be used in compliance with applicable federal, state, provincial, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and materials to be handled. OPW MAKES NO WARRANTY OF FITNESS FOR A PARTICULAR USE. All illustrations and specifications in this literature are based on the latest product information available at the time of publication. OPW reserves the right to make changes at any time in prices, materials, specifications and models and to discontinue models without notice or obligation.



### 444TA AST Four Signal Tank Alarm (444TA)



The OPW 444TA AST Remote Four Signal Tank Alarm is designed to sense up to four different liquid levels or other signals using just one device. Both audible and visual indicators are used to ensure reliable notifications.

## OPW 444TA Tank Alarm

---

### Features

- **Up to four alarm signals** - That can be used for high or low liquid level sensing, interstitial monitoring, and/or other signals in one to four separate tanks.
- **Relay Option** - Trigger another alarm, pump, switch, or other device from this alarm unit.
- **Self-powered** - Lithium battery with a 10-year shelf life for long service life.
- **Audible Alarm** - Sounds a 90-decibel alarm at 4 feet away.
- **Float Switch Sub-Assembly** - Uses all Stainless Steel construction that allows use in an array of fluid applications.
- **Product / Alarm Identification Label** - Located on top of the alarm for quick and easy identification, allowing you to correspond alarms to signals. Label has a protective covering.
- **Intrinsically Safe** - Complies with ANSI/UL 913 for Class 1, Division 1 & 2 for Groups C & D hazardous locations.
- **Cold Weather Resistant** - All components are safe for temperatures down to -40 degrees operation (and up to 120 degree F).

### Materials

Enclosure: Polybutylene Terephthalate

Wire Grommet: Nylon w/ Buna Seal

Float Switch: Closed Cell Buna Float & Stainless Steel Rod

Pipe: Stainless Steel

Tank Adaptor: Stainless Steel

### Certified

Conforms to ANSI/UL STD 913

Certified to CAN/CSA

STD C22.2 No. 157-92

Florida EQ-610

## Certifications

---



## 444TA Ordering Specifications

---

Product	Description	lb.	kg
444TA-0100	Four Signal Tank Alarm Box, No Float Switches	4	1.8
44TA-LLFS	36" Adjustable Float Level Switch Sub-Assembly	0	0.0
TGTA-0400*	4" Tank Bung Gauge and Alarm Combo Fitting (OPW 61T required for use)	10	4.5

\* TGTA-0400 4" Tank Bung Combo Fitting / Note: Drop Tube must be used with TGTA-0400

## Dimensions

---

	in.	cm
A	5 1/32"	12.8
B	5 1/32"	12.8
C	4 3/16"	10.6

## 444TA

Product Alarm  
I.D. Label

