

K800™ Hybrid Fuel Control System

K800™ Hybrid Fuel Control System Features

- Windows-based ARTWare™ PC software makes programming simple and provides system backup
- System management easily performed on-site or remotely via dial up, cell phone modem, LAN/WAN, or Bluetooth™
- Compatible with optional FleetLink™ RFID system, allowing vehicle I.D., mileage and other information to be automatically captured through the fuel nozzle at the vehicle's fuel fill tube
- Pump and product totals automatically or on demand
- System can be set to track the mechanical pump totalizers
- Daily and monthly allocation amounts
- Sixteen quantity restriction levels
- Sixteen product restriction combinations
- Odometer or hourmeter recording
- User can be prompted to enter miscellaneous data of up to ten digits (job, vehicle, driver ID, etc.)
- Single or dual card/key/cardless entry operation (driver/vehicle number)
- Cards can be assigned to accounts or departments
- Card/key/account lockout
- Programmable K800™ Fuel Island Terminal displays messages and user prompts
- A price may be assigned to each product to be recorded for each transaction
- Standard system utilizes magnetic cards
- ChipKey® mileage and reasonability assures accurate mileage entry
- Optional proximity card reader
- Programmable system open/close times
- Password protection for ultimate security
- Self-test and diagnostic utilities for start-up and troubleshooting
- Office journal printer for transaction logging
- USB key for transaction information backup and card updates
- Optional Bluetooth™ or cell modem communication for remote sites
- Optional 900 MHz wireless communication between island and building
- The K800™ Hybrid System interfaces with many commercial fueling networks

Memory

- Standard memory 2,000 proprietary cards, and 500 transactions
- Expandable to 64,000 proprietary cards, and 2,000 transactions

Pump Control Methods

- Pump Control Modules for Commercial Dispensers with mechanical registers
 - Mounted in Fuel Island Terminal for low-cost, convenient wiring
 - Mounted in remote cabinet
 - Pump Handle Monitor
 - Manual bypass for each dispenser
 - Four adjustable fueling timers
 - Maximum fueling time
 - Maximum time to activate pump handle
 - Maximum time until first pulse
 - Maximum time between pulses

- Counts in gallons or litres from thousandths to full units
- Pump sentry provides protection from faulty pulsers
- Direct Pump Control communicates via serial link to the dispensers (Optional)
 - Supports Wayne, Gilbarco and Tokheim protocols
 - Extremely simple installation
- Universal Pump Controller for operation with a pump controller (Optional)
 - Interfaces with Wayne, Gilbarco and Tokheim
 - Allows pumps to be controlled via the Fuel Island Terminal or retail pump console

Phoenix™ Software

- Phoenix™ Plus – poll transactions, perform card updates, run reports
- Phoenix™ Premier – all of the Phoenix™ Plus features, plus tank gauge interface for reconciliation

K800™ Hybrid Fuel Island Terminal Specifications

Readers (any one of the following):

- Magnetic-Stripe Card
- ChipKey®
- HID Proximity Card/Key (Optional)

Display: 2 line x 16 character Backlit LCD

Enclosure Dimensions: 12" H x 13" W x 10" D
(30.5 cm H x 33 cm W x 25.5 cm D)

Power Requirements: 120/230 VAC 50-60 Hz 100 watts Max.

Operating Temperature: -40° F to 122° F (-40° C to 50° C)

Pump Control Terminal Specifications

Relay Rating: 1 HP, 120/240 VAC

Pulser Compatibility: Contact/12 VDC Electronic

Pulser Power Supply: 12 VDC; 40 milliamps max./pulser

Pulser Speed: 6,000 pulses/minute (mechanical)

100,000 pulses per minute (electronic)

Pulser Rate: 1:1 to 9,999:1 (in one-pulse increments)

Pulser Type: Single channel

Pulser Duty Cycle: 50%

Operating Temperature Range: -40° F to 122° F (-40° C to 50° C)

FSC3000™ Fuel Site Controller Specifications

Dimensions: 2" H x 10" W x 11" D (5 cm H x 25 cm W x 28 cm D)

Power Requirements: 85-240 VAC, 50/60 Hz; 25 watts max.

Operating Temperature Range (indoors): 32° F to 122° F
(0° C to 50° C)

Serial Communication Ports: Petro-Net™ (RS-485), Printer (RS-232),

Terminal (RS-232), Modem (RS-232), Pass-through (RS-232),

2 Auxiliary Ports (RS-232), Tank Gauge, Ethernet, USB

Maximum Petro-Net™ Distance: 5,000 feet (1524 m)



ONE COMPANY. ONE WORLD. ONE SOURCE.

6900 SANTA FE DRIVE • HODGKINS, IL USA 60525 • www.opwfms.com • 708-485-4200 • (fax) 708-485-4630

NOTE: All information subject to engineering and/or other changes. All trade names are copyrighted. Patents Pending. ©2008 OPW Fuel Management Systems
©2008 Delaware Capital Formation, Inc. All Rights Reserved. DOVER and the DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation